

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : All Weather Seal
Product code : 468-9130-16

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Sealant
Recommended use : Intended for general public

1.4. Supplier's details

Supplier

Ironite Products Inc.
2525 18th Street SW, Suite D
Cedar Rapids, Iowa 52404
T (319) 377-9421 or 1-800-553-5953
service@irontite.com

1.5. Emergency phone number

Emergency number : 1-800-553-5953 8am-4pm CST(GMT - 6)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 1	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	Causes serious eye damage.
Reproductive toxicity, Category 1B	May damage fertility or the unborn child.
Specific target organ toxicity — Single exposure, Category 1	Causes damage to organs.
Health hazard not otherwise classified, Category 1	Causes severe damage to the respiratory tract.

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Causes severe skin burns and eye damage
May damage fertility or the unborn child
Causes damage to organs.
Causes severe damage to the respiratory tract.

Precautionary statements (GHS US) :

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Do not breathe dusts or mists.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
If exposed or concerned: Call a poison center or doctor.
If swallowed: rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Take off immediately all contaminated clothing and wash it before reuse.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Store locked up.
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Inorganic Borate	CAS-No.: Trade Secret	Trade Secret
Talc	CAS-No.: Trade Secret	Trade Secret
Caustic Base 1	CAS-No.: Trade Secret	Trade Secret
Ethylene glycol	CAS-No.: 107-21-1	1 – 5
Caustic Base 2	CAS-No.: Trade Secret	Trade Secret

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Call a POISON CENTER or doctor/physician.
First-aid measures after inhalation : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a poison center or doctor/physician.

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after inhalation	: Causes severe damage to the respiratory tract.
Symptoms/effects after skin contact	: Causes severe skin burns. Symptoms may include redness, pain, blisters.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: May damage fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. Products of combustion may include, and are not limited to: oxides of carbon. Metal oxides. Toxic fumes may be released.
Explosion hazard	: No direct explosion hazard.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

For non-emergency personnel

Emergency procedures	: Do not touch or walk on the spilled product.
----------------------	--

For emergency responders

Environmental precautions	: Avoid release to the environment. Prevent entry to sewers and public waters.
---------------------------	--

6.2. Methods and materials for containment and cleaning up

For containment	: Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
-----------------	---

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Store away from other materials. Provide ventilation.

For further information refer to section 13, For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, fume, gas, mist, spray, vapors. Do not get in eyes, on skin, or on clothing. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Ensure good ventilation of the work station. Avoid contact during pregnancy/while nursing.

Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep out of reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Store locked up.

Incompatible materials : Oxidizing materials. Sources of ignition. Direct sunlight. Strong bases. Strong acids.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Inorganic Borate (Trade Secret)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	2 mg/m ³ (inhalable particulate matter (Borate compounds, inorganic))
ACGIH OEL STEL	6 mg/m ³ (inhalable particulate matter (Borate compounds, inorganic))
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	5 mg/m ³
Talc (Trade Secret)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
ACGIH chemical category	Not Classifiable as a Human Carcinogen containing no asbestos fibers
USA - OSHA - Occupational Exposure Limits	
Local name	Talc (not containing asbestos) (Silicates (less than 1% crystalline silica))
OSHA PEL TWA	20 mppcf (if 1% Quartz or more, use Quartz limit)
OSHA PEL TWA	20 mppcf
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - IDLH - Occupational Exposure Limits	
IDLH	1000 mg/m ³ (containing no asbestos and <1% quartz)

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Talc (Trade Secret)	
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	2 mg/m ³ (containing no Asbestos and <1% Quartz-respirable dust)
Ethylene glycol (107-21-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethylene glycol
ACGIH OEL TWA	25 ppm (vapor fraction)
ACGIH OEL STEL	10 mg/m ³ (inhalable particulate matter, aerosol only)
ACGIH OEL STEL	50 ppm (vapor fraction)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2024
Caustic Base 2 (Trade Secret)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL Ceiling	2 mg/m ³
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	2 mg/m ³
USA - IDLH - Occupational Exposure Limits	
IDLH	10 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (Ceiling)	2 mg/m ³
US-NIOSH chemical category	SK: DIR(COR) Apr 2011

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.
Eye protection:
Wear eye/face protection
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available.
Color	: Gray
Odor	: Odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.2 g/cm ³
Solubility	: Easily soluble in the following materials: cold water and hot water.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

Talc	
Vapor pressure	0 Pa Temp.: 25 °C Remarks on result: 'other:'
Particle characteristics	No data available

Caustic Base 1	
Boiling point	119 °C
Vapor pressure	17 hPa (at 24 °C)
Particle characteristics	No data available

Ethylene glycol	
Boiling point	197.3 °C (at 1013 hPa)
Flash point	115 °C (open cup)
Auto-ignition temperature	398 °C
Vapor pressure	0.1 hPa (at 20 °C)
Particle characteristics	No data available

Caustic Base 2	
Boiling point	1390 °C
Vapor pressure	0 hPa (at 20 °C)
Particle characteristics	No data available

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : 10 % (w/w)

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Incompatible materials. Heat.

10.5. Incompatible materials

Oxidizing materials. Strong acids. Strong bases.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Metal oxides. Toxic fumes may be released.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Inorganic Borate (Trade Secret)	
LD50 oral rat	3493 mg/kg (Source: NZ_CCID)
LD50 oral	4450 mg/kg
LD50 dermal rabbit	> 10000 mg/kg (Source: JAPAN_GHS)
LC50 inhalation rat	> 2 mg/m ³ (Exposure time: 4 h Source: NLM_HSDB)
Talc (Trade Secret)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat	> 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Ethylene glycol (107-21-1)	
LD50 oral rat	4700 mg/kg (Source: NLM_CIP)
LD50 oral	6140 mg/kg

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Ethylene glycol (107-21-1)	
LD50 dermal rat	10600 mg/kg (Source: JAPAN_GHS)
LD50 dermal	9530 mg/kg
LC50 inhalation rat	> 2.5 mg/l (Exposure time: 6 h Source: ECHA_API)
Caustic Base 2 (Trade Secret)	
LD50 oral rat	325 mg/kg (Source: OECD_SIDS)
LD50 dermal rabbit	1350 mg/kg (Source: NLM_HSDB)
Skin corrosion/irritation	: Causes severe skin burns.
Caustic Base 2 (Trade Secret)	
pH	12 (conc: 0.05 % (solution))
Serious eye damage/irritation	: Causes serious eye damage.
Caustic Base 2 (Trade Secret)	
pH	12 (conc: 0.05 % (solution))
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Talc (Trade Secret)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
Ethylene glycol (107-21-1)	
NOAEL (chronic,oral,animal/male,2 years)	1500 mg/kg body weight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: Causes damage to organs.
Inorganic Borate (Trade Secret)	
STOT-single exposure	May cause respiratory irritation.
Ethylene glycol (107-21-1)	
STOT-single exposure	Causes damage to organs. May cause respiratory irritation.
Caustic Base 2 (Trade Secret)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Talc (Trade Secret)	
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Aspiration hazard	: Not classified
All Weather Seal	
Viscosity, kinematic	No data available

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Inorganic Borate (Trade Secret)	
Viscosity, kinematic	No data available

Talc (Trade Secret)	
Viscosity, kinematic	No data available

Caustic Base 1 (Trade Secret)	
Viscosity, kinematic	No data available

Ethylene glycol (107-21-1)	
Viscosity, kinematic	14.465 mm ² /s

Caustic Base 2 (Trade Secret)	
Viscosity, kinematic	No data available

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after inhalation	: Causes severe damage to the respiratory tract.
Symptoms/effects after skin contact	: Causes severe skin burns. Symptoms may include redness, pain, blisters.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: May damage fertility or the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Inorganic Borate (Trade Secret)	
LC50 - Fish [1]	501 mg/l

Talc (Trade Secret)	
LC50 - Fish [1]	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'

Ethylene glycol (107-21-1)	
LC50 - Fish [1]	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)
EC50 - Crustacea [1]	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	14 – 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Ethylene glycol (107-21-1)	
EC50 96h - Algae [1]	6500 – 13000 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [2]	6500 – 13000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
NOEC chronic crustacea	4.2 mg/l

Caustic Base 2 (Trade Secret)	
LC50 - Fish [1]	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)
EC50 - Crustacea [1]	40 mg/l

12.2. Persistence and degradability

All Weather Seal	
Persistence and degradability	Not established.

Inorganic Borate (Trade Secret)	
Persistence and degradability	Rapidly degradable

Talc (Trade Secret)	
Persistence and degradability	Rapidly degradable

Caustic Base 1 (Trade Secret)	
Persistence and degradability	Rapidly degradable

Ethylene glycol (107-21-1)	
Persistence and degradability	Rapidly degradable

Caustic Base 2 (Trade Secret)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

All Weather Seal	
Bioaccumulative potential	Not established.

Talc (Trade Secret)	
BCF - Fish [1]	(no known bioaccumulation)

Ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water	-1.36

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

Other information : Avoid release to the environment. No other effects known.

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.

SECTION 14 Transport information

In accordance with DOT

14.1. UN number

Not regulated for transport

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not regulated

14.4. Packing group

Packing group (DOT) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

Not applicable

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. State regulations

WARNING:

This product can expose you to chemicals including o-Phenylphenate, which is known to the State of California to cause cancer, and Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

All Weather Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Revision date : 2/20/2025
Issue date : 9/4/2018
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Indication of changes:			
Section	Changed item	Comments	Version
SDS update	SDS update	Modified	V2.0

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.