



Main

| | |
|-------------------------------------|--|
| Range | TeSys |
| Product or component type | Differential thermal overload relay |
| Relay application | Motor protection |
| Network type | AC DC |
| Thermal protection adjustment range | 9...13 A |
| [Ui] rated insulation voltage | 600 V power circuit conforming to CSA 600 V power circuit conforming to UL 690 V power circuit conforming to IEC 60947-4-1 |

Complementary

| | |
|--|---|
| Network frequency | 0...400 Hz |
| Mounting support | Plate with specific accessories Rail with specific accessories Under contactor |
| Tripping threshold | 1.14 +/- 0.06 I _r conforming to IEC 60947-4-1 |
| [I _{th}] conventional free air thermal current | 5 A for signalling circuit |
| Permissible current | 3 A at 120 V AC-15 for signalling circuit 0.22 A at 125 V DC-13 for signalling circuit |
| [U _e] rated operational voltage | 690 V AC 0...400 Hz |
| [U _{imp}] rated impulse withstand voltage | 6 kV |
| Phase failure sensitivity | Tripping current 130 % of I _r on two phase, the last one at 0 |
| Control type | Red push-button stop |

| | |
|--------------------------|---|
| | Blue push-button for reset mode |
| Temperature compensation | -20...60 °C |
| Connections - terminals | Control circuit : screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible without cable end Control circuit : screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible with cable end Control circuit : screw clamp terminals 2 cable(s) 1...2.5 mm ² solid without cable end Power circuit : screw clamp terminals 1 cable(s) 1.5...10 mm ² flexible without cable end Power circuit : screw clamp terminals 1 cable(s) 1...4 mm ² flexible with cable end Power circuit : screw clamp terminals 1 cable(s) 1...6 mm ² solid without cable end |
| Tightening torque | Control circuit : 1.7 N.m on screw clamp terminals Power circuit : 1.7 N.m on screw clamp terminals |
| Width | 45 mm |
| Depth | 70 mm |
| Product weight | 0.124 kg |

Environment

| | |
|---------------------------------------|---|
| Protective treatment | TH conforming to IEC 60068 |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Ambient air temperature for operation | -20...60 °C without derating conforming to IEC 60947-4-1 |
| Ambient air temperature for storage | -60...70 °C |
| Flame retardance | V1 conforming to UL 94 |
| Mechanical robustness | Vibrations 6 Gn IEC 60068-2-6 Shocks 15 Gn for 11 ms IEC 60068-2-7 |
| Dielectric strength | 6 kV at 50 Hz conforming to IEC 60255-5 |
| Standards | ATEX D 94/9/CE EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| Product certifications | ATEX INERIS BV CCC CSA DNV GL GOST LROS (Lloyds register of shipping) RINA UL |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0631 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product Environmental Profile |
| Product end of life instructions | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|